
SmartFlex™


With over 100 possible configurations, it's smart to get exactly what you need.








With hundreds of possible configurations, flexible SmartFlex cellular routers can be configured to suit any application.





- + Aggregate data from multiple devices: Serial, Ethernet, Wi-Fi, I/O.
- + Standard ports include (2) Ethernet, (1) I/O port, (1) USB port, (2) SIM slots and (1) MicroSD card holder.
- + Optional ports include additional Ethernet ports and RS-232/422/485 serial ports with isolation.
- + The router may have up to (5) Ethernet ports (2 Router, 3 Ethernet Switch).
- + Optional, industrial grade Wi-Fi is available.
- + GPS and GLONASS support.
- + Plastic or Metal Enclosure.
- + PoE models available.
- + Install our User Modules for specific applications or create your own.
- + Switch between cellular carriers at a moment's notice.
- + Connect Modbus equipment.

Intelligent

- Download our User Modules for specialized functions. Use the router as an AT Modem Emulator, a Modbus RTU/ TCP gateway and more.
- + Create your own Linux scripts for additional special functions.
- + Create multiple software configurations for each router, and switch between them at any time.
- + Upgrade router configuration and firmware from your central server, allowing for simultaneous mass reconfiguration of every router on the network.
- + Use a secure Web interface to configure and manage the SmartFlex[™] from remote locations.
- + Low power consumption mode for solar and battery power applications.

Powerful

- + Full support for LTE
- + 256 MB flash memory, 512 MB RAM and 128kB M-RAM
- + Upload speeds of up to 50 Mbit/s and download speeds of up to 100 Mbit/s easily handles video applications.

Safe and Secure

- + Real time data encryption and the creation of VPN tunnels using IPsec, OpenVPN and L2TP.
- + Support for DHCP, NAT, NAT-T, DynDNS, NTP, VRRP, control by SMS and numerous other functions.

Rugged and Reliable

- + Dual SIM card ports for automatic failover or multiple cellular carrier support.
- + Designed and manufactured for use in tough environmental conditions.
- + Extended operational temperature range from -40 °C to +75 °C.
- + 10-60 VDC operation with transient and reverse polarity voltage protection.
- + Industrial certifications.

Port Configurations & Options

		STANDARD CONFIGURATIONS					OPTIONAL PORT CONFIGURATIONS				
MODEL NO.		LTE ROUTER	GPS	2X ETHERNET (router port)	USB	1/0	RS232 RS485/422	RS232/485 ETHERNET	3X ETHERNET (switch)	WI-FI	POE
	SR30xxxx0xx	✓		✓	✓	✓			✓	✓	✓
	SR30xxxx0xx	✓	✓	✓	✓	✓					✓
	SR30xxxx1xx	✓	✓	✓	✓	✓			✓	✓	✓
	SR30xxxx3xx	✓	✓	✓	✓	✓	✓			✓	✓
	SR30xxxx4xx	✓	✓	✓	✓	✓		✓		✓	✓

+ GLOBAL REACH FOR GLOBAL SUPPORT

You build your business and we will build your communication solution. Whether you need standard products or require special designs for specific applications – B+B SmartWorx can help.

B+B SMARTWORX

Powered by



Worldwide Headquarters

ADVANTECH No.1, Alley20, Lane26, Rueiguang Road Neihu District, Taipei 11491 Taiwan, R.O.C Phone: 0800-777-111 www.advantech.com

European Headquarters

Oranmore, Co. Galway, Ireland Phone: +353 91 792444 Fax: +353 91 792445 eSales@advantech-bb.com

Corporate Headquarters

707 Dayton Road Ottawa, IL 61350 USA Phone: 1-815-433-5100 Fax: 1-815-433-5109 orders@advantech-bb.com www.advantech-bb.com

Middle East, UAE, Africa

mdeast-afrsales@advantech-bb.com Mobile: +971 50 943 65 62 AG Silver Tower, JLT, P.O. Box 48777 Dubai, UAE

Cellular Product Group

Sokolská 71, 562 04 Ústí nad Orlicí III. Czech Republic Phone: +420 465 521 020 Fax: +420 464 647 299 GSM: +420 603 872 287 cellularsales@advantech-bb.com

Latin America, Carribean

latamsales@advantech-bb.com Phone: 1-727-797-0300 Cell: 1-727-480-5920

OEM & Product Modification

Phone: 815-433-5222 Fax: 815-433-5104 Attn: Custom Dept. custom@advantech-bb.com Custom Quote Request Form: http://advantech-bb.com/custom